



PRODUCT NAME: JIGGA

PRODUCT DESCRIPTION: Thermotrak heat resistant non-metallic work boot

INFORMATION

COLOUR	Black
SIZE RANGE	3 – 13 (unisex, starts from a size 3)
ISO 20345 CLASSIFICATION	SBP – no anti-static properties; anti-penetration; WRU water resistant upper
SLIP RESISTANCE CLASSIFICATION SRA / SRB / SRC	SRA – tested for slip resistance in environments of ceramic surfaces with soapy solution
CONSTRUCTION	Injection moulded construction process
NRCS APPROVAL NO	NRCS/9002/262020/0102

MATERIALS

UPPER	High quality full grain barton print leather with water resistant coating and has a thermoplastic polyurethane toe bumper for added scuff protection
SOLE	Dual density polyurethane (PU) and rubber outsole, with a non-metallic high-density mesh midsole for anti-penetration protection
EYELETS	Non-metallic high density plastic
LINING	Breathable and abrasion resistant taibrelle
TOE CAP	200J composite non-metallic toe cap
FOOTBED (INSOLE)	Moulded polyurethane (PU); taibrelle mesh upper with contoured heel and arch
INSOLE BOARD	3MR Ibitech non-woven insole board

SPECIAL FEATURES

UPPER	<ul style="list-style-type: none"> • 200J composite non-metallic toe cap • Water resistant upper
MIDSOLE	Non-metallic high-density mesh for anti-penetration
SOLE	Outsole is heat resistant up to 300°C
OTHER	No breakdown at AC voltage raised at 5kVs per minute up to 20Kv and held for 60 seconds. Compliant with ESKOM SPEC 34-232

KEY FEATURES



SUGGESTED ENVIRONMENTS

Electricians, engineering, mining, chemical and petrochemical, refineries, welders/foundries and smelters.